

256 Positions Attenuator

Item Quantity Reference Part

1	1	C1	104P 藍色積層電容無極性
2	1	C2	100uF/25V
3	1	J1	XH254_10P
4	1	J3	CON2
5	2	J4,J5	XH254_3P
6	8	K1,K2,K3,K4,K5,K6,K7,K8	EA2-12NU
7	2	P1,P2	PAD
8	1	Q1	BC550 備用
9	32	R1,R2,R3,R4,R5,R6,R7,R8, R9,R10,R11,R12,R13,R14, R15,R16,R17,R18,R19,R20, R21,R22,R23,R24,R25,R26, R27,R28,R30,R32,R33,R34	R
10	2	R29,R31	N/C
11	1	R35	10K 備用
12	1	PCB	150mm x 50mm

PA09 SOURCE SELECT

1	2	C1,C2	220UF SMD 鉭電容 標線為 + 選配
2	1	C3	10UF SMD 選配
3	3	D1,D2,D3	RLS4148 選配
4	2	JP1,JP2	JUMP/K8
5	2	J1,J4	CON3
6	1	J3	XH254_3P 選配
7	1	J2	XH254_9P
8	8	K1,K2,K3,K4,K5,K6,K7	EA2-12NU K8 選配
9	2	Q1,Q2	NPN SMD 選配
10	16	RCA1,RCA2,RCA3,RCA4,RCA5, RCA6,RCA7,RCA8,RCA9, RCA10,RCA11,RCA12,RCA13,	自理

RCA14,RCA15,RCA16

11	4	R1,R2,R3,R5	10K SMD 0805 選配
12	1	R4	22K or 47K SMD 0805 選配
13	1	PCB	220mm x 50mm

256 Positions Attenuator M.C.U

1	7	C1,C2,C4,C6,C7,C8,C9	100NF/X7R SMD
2	2	C3,C5	100UF SMD 鉭電容 標線為 +
3	1	D1	RLS4148 SMD
4	1	J2	XH254_5P 配排線
5	1	J3	XH254_10P 配排線
6	1	J4	XH254_9P 配排線
7	1	J1	CON2
8	1	LCD1	1602-5
9	1	Q1	DTC114EK SMD
10	1	R1	100R SMD 0805
11	1	R2	22K SMD 0805
12	1	R4	PR10K 排阻 標點為共用腳這接 VDD (朝 2019 方向)
13	4	S1,S2,S3,S4	SW SPST 依購買機殼自理
14	1	U1	16F685A
15	2	U2,U4	ULN2004
16	1	U3	74HC238
17	1	U6	VS1838B
18	1	U5	7805
19	1	H1	HEATSINK
20	1	PCB	100mm x 50 mm